



Figure similar

*** spare part *** SIMATIC DP, interface module IM 151-1 Standard for ET 200S; incl. termination module data volume of 244 bytes each for inputs and outputs; max. 63 I/O modules PROFIBUS DP V0 and V1 up to 2 m width can be connected; bus connection via 9-pin D-sub

General information	
Product type designation	IM 151-1 ST
Vendor identification (VendorID)	806Ah
Product function	
• Isochronous mode	No
Supply voltage	
Mains buffering	
• Mains/voltage failure stored energy time	20 ms
Input current	
from supply voltage 1L+, max.	200 mA
Power loss	
Power loss, typ.	3.3 W
Address area	
Addressing volume	
• Inputs	244 byte
• Outputs	244 byte
Interfaces	
Transmission procedure	RS 485
Transmission rate, max.	12 Mbit/s; 9,6 / 19,2 / 45,45 / 93,75 / 187,5 / 500 kbit/s; 1,5 / 3 / 6 / 12 Mbit/s
PROFIBUS DP	
• Cable length, max.	1 200 m
1. Interface	
Interface types	
• RS 485	Yes
• Output current of the interface, max.	80 mA
• Design of the connection	9-pin sub D socket
Protocols	
Supports protocol for PROFINET IO	No
PROFIBUS DP	Yes
PROFIBUS DP	
Services	
— SYNC capability	Yes
— FREEZE capability	Yes
— Direct data exchange (slave-to-slave communication)	Yes
Interrupts/diagnostics/status information	
Alarms	Yes
Diagnostics function	Yes
Diagnostics indication LED	

- Bus fault BF (red) Yes
- Group error SF (red) Yes
- Monitoring 24 V voltage supply ON (green) Yes

Potential separation

between backplane bus and electronics	No
between electronic block and PROFIBUS DP	Yes
between supply voltage and electronics	No

Isolation

Isolation tested with	500 V DC
-----------------------	----------

Standards, approvals, certificates

CE mark	Yes
UL approval	Yes

Ambient conditions

Ambient temperature during operation	
• min.	0 °C
• max.	60 °C

Dimensions

Width	45 mm
Height	119.5 mm
Depth	75 mm

Weights

Weight, approx.	150 g
-----------------	-------

last modified: 8/11/2023 