

Data sheet

6ES7134-4NB51-0AB0



SIMATIC DP, Electronics module ET 200S: 2AI RTD High Feature, 15 mm width, 15 bit+sign accuracy +/-0.1%, for 2-/3-/4-wire sensors, with internal compensation of the line resistance, with SF LED (group fault)

General information

Product function

- Isochronous mode

No

Supply voltage

Load voltage L+

- | | |
|-------------------------------|-------------------------|
| • Rated value (DC) | 24 V; From power module |
| • Reverse polarity protection | Yes |

Input current

from load voltage L+ (without load), max.

30 mA

from backplane bus 3.3 V DC, max.

10 mA

Power loss

Power loss, typ.

0.6 W

Address area

Address space per module

- | | |
|----------------------------------|--------|
| • Address space per module, max. | 4 byte |
|----------------------------------|--------|

Analog inputs

Number of analog inputs

2

permissible input voltage for voltage input (destruction limit), max.

9 V

Constant measurement current for resistance-type transmitter, typ.

1.25 mA

Cycle time (all channels) max.

Number of active channels per module x basic conversion time

Technical unit for temperature measurement adjustable

Yes

Input ranges (rated values), resistance thermometer

- | | |
|---|--------------|
| • Cu 10
— Input resistance (Cu 10) | Yes
10 MΩ |
| • Ni 100
— Input resistance (Ni 100) | Yes
10 MΩ |
| • Ni 1000
— Input resistance (Ni 1000) | Yes
10 MΩ |
| • Ni 120
— Input resistance (Ni 120) | Yes
10 MΩ |
| • Ni 200
— Input resistance (Ni 200) | Yes
10 MΩ |
| • Ni 500
— Input resistance (Ni 500) | Yes
10 MΩ |
| • Pt 100
— Input resistance (Pt 100) | Yes
10 MΩ |
| • Pt 1000
— Input resistance (Pt 1000) | Yes
10 MΩ |

• Pt 200	Yes
— Input resistance (Pt 200)	10 MΩ
• Pt 500	Yes
— Input resistance (Pt 500)	10 MΩ
Input ranges (rated values), resistors	
• 0 to 150 ohms	Yes
— Input resistance (0 to 150 ohms)	10 MΩ
• 0 to 300 ohms	Yes
— Input resistance (0 to 300 ohms)	10 MΩ
• 0 to 600 ohms	Yes
— Input resistance (0 to 600 ohms)	10 MΩ
• 0 to 3000 ohms	Yes
— Input resistance (0 to 3000 ohms)	10 MΩ
Thermocouple (TC)	
Temperature compensation	
— internal temperature compensation	Yes
Characteristic linearization	
• parameterizable	Yes; for Pt _{xxx} , Ni _{xxx}
— for resistance thermometer	Pt _{xxx} , Ni _{xxx}
Cable length	
• shielded, max.	200 m
Analog value generation for the inputs	
Measurement principle	integrating (Sigma-Delta)
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit; for Pt100, Ni100, Ni120, Pt200, Ni200, Pt500, Ni500, Pt1000, Ni1000, Cu10: 15 bit + sign; for 150, 300, 600, 3 000 ohms: 15 bit; for PTC: 1 bit
• Integration time (ms)	16,7 / 20 ms
• Interference voltage suppression for interference frequency f ₁ in Hz	50 / 60 Hz
• Conversion time (per channel)	Basic conversion time incl. integration time: 50 / 60 ms; additional conversion time for diagnostics of wire break test: 5 / 5 ms; additional conversion time for line compensation with 3-wire connection: 50 / 60 ms
Smoothing of measured values	
• parameterizable	Yes; In four stages by means of digital filtering
• Step: None	Yes; 1x cycle time
• Step: low	Yes; 4x cycle time
• Step: Medium	Yes; 32x cycle time
• Step: High	Yes; 64x cycle time
Encoder	
Connection of signal encoders	
• for resistance measurement with two-wire connection	Yes
• for resistance measurement with three-wire connection	Yes; internal compensation of the line resistances
• for resistance measurement with four-wire connection	Yes
Errors/accuracies	
Operational error limit in overall temperature range	
• Resistance thermometer, relative to input range, (+/-)	Resistance-type transmitter: ±0.1 %; Pt100, Pt200, Pt500, Pt1000 standard: ±1.0 K; Pt100, Pt200, Pt500, Pt1000 climate: ±0.25 K; Ni100, Ni120, Ni200, Ni500, Ni1000 standard and climate: ±0.4 K; Cu10 ±1.5 K
Basic error limit (operational limit at 25 °C)	
• Resistance thermometer, relative to input range, (+/-)	Resistance-type transmitter: ±0.05 %; Pt100, Pt200, Pt500, Pt1000 standard: ±0.6 K; Pt100, Pt200, Pt500, Pt1000 climate: ±0.13 K; Ni100, Ni120, Ni200, Ni500, Ni1000 standard and climate: ±0.2 K; Cu10 ±1 K
Interrupts/diagnostics/status information	
Diagnoses	
• Wire-break	Yes
• Group error	Yes
• Overflow/underflow	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
Parameter	
Remark	7 byte
Diagnostics wire break	Disable / enable
Group diagnostics	Disable / enable

Overflow/underflow	Disable / enable
Potential separation	
Potential separation analog inputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	40 g

last modified:

8/16/2023 