



Figure similar

\*\*\*\*\* Replacement part \*\*\*\*\* SIMATIC S7-400, CPU 414-2 Central processing unit with: work memory 1 MB, (0.5 MB code, 0.5 MB data), 1st interface MPI/DP 12 Mbit/s, 2nd interface PROFIBUS DP

General information	
Product type designation	CPU 414-2
HW functional status	03
Firmware version	V5.3
Product function	
<ul style="list-style-type: none"> <li>• Isochronous mode</li> </ul>	Yes; For PROFIBUS only
Engineering with	
<ul style="list-style-type: none"> <li>• Programming package</li> </ul>	STEP 7 V5.3 SP2 or higher with HW update
CiR - Configuration in RUN	
CiR synchronization time, basic load	100 ms
CiR synchronization time, time per I/O byte	15 µs
Supply voltage	
Rated value (DC)	Power supply via system power supply
Input current	
from backplane bus 5 V DC, typ.	0.9 A
from backplane bus 5 V DC, max.	1.1 A
from backplane bus 24 V DC, max.	300 mA; 150 mA per DP interface
from interface 5 V DC, max.	90 mA; At each DP interface
Power loss	
Power loss, typ.	4.5 W
Power loss, max.	5 W
Memory	
Type of memory	RAM
Work memory	
<ul style="list-style-type: none"> <li>• integrated</li> <li>• integrated (for program)</li> <li>• integrated (for data)</li> <li>• expandable</li> </ul>	1 Mbyte 0.5 Mbyte 0.5 Mbyte No
Load memory	
<ul style="list-style-type: none"> <li>• expandable FEPR0M</li> <li>• expandable FEPR0M, max.</li> <li>• integrated RAM, max.</li> <li>• expandable RAM</li> <li>• expandable RAM, max.</li> </ul>	Yes; with Memory Card (FLASH) 64 Mbyte 512 kbyte Yes; with Memory Card (RAM) 64 Mbyte
Backup	
<ul style="list-style-type: none"> <li>• present</li> <li>• with battery</li> <li>• without battery</li> </ul>	Yes Yes; all data No
Battery	

<b>Backup battery</b>	
• Backup current, typ.	125 µA; up to 40 °C
• Backup current, max.	550 µA
• Backup time, max.	See reference manual, module data, Chapter 3.3
• Feeding of external backup voltage to CPU	5 V DC to 15 V DC
<b>CPU processing times</b>	
for bit operations, typ.	45 ns
for word operations, typ.	45 ns
for fixed point arithmetic, typ.	45 ns
for floating point arithmetic, typ.	135 ns
<b>CPU-blocks</b>	
<b>DB</b>	
• Number, max.	6 000; Number range: 1 to 16000
• Size, max.	64 kbyte
<b>FB</b>	
• Number, max.	3 000; Number range: 0 to 7999
• Size, max.	64 kbyte
<b>FC</b>	
• Number, max.	3 000; Number range: 0 to 7999
• Size, max.	64 kbyte
<b>OB</b>	
• Number, max.	see instruction list
• Size, max.	64 kbyte
• Number of free cycle OBs	1; OB 1
• Number of time alarm OBs	4; OB 10-13
• Number of delay alarm OBs	4; OB 20-23
• Number of cyclic interrupt OBs	4; OB 32-35 (shortest cycle that can be set = 500 µs)
• Number of process alarm OBs	4; OB 40-43
• Number of DPV1 alarm OBs	3; OB 55-57
• Number of isochronous mode OBs	3; OB 61-63
• Number of multicomputing OBs	1; OB 60
• Number of background OBs	1; OB 90
• Number of startup OBs	3; OB 100-102
• Number of asynchronous error OBs	9; OB 80-88
• Number of synchronous error OBs	2; OB 121, 122
<b>Nesting depth</b>	
• per priority class	24
• additional within an error OB	1
<b>Counters, timers and their retentivity</b>	
<b>S7 counter</b>	
• Number	2 048
<b>Retentivity</b>	
— adjustable	Yes
— preset	Z 0 to Z 7
<b>Counting range</b>	
— lower limit	0
— upper limit	999
<b>IEC counter</b>	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
<b>S7 times</b>	
• Number	2 048
<b>Retentivity</b>	
— adjustable	Yes
— preset	No times retentive
<b>Time range</b>	
— lower limit	10 ms
— upper limit	9 990 s
<b>IEC timer</b>	

<ul style="list-style-type: none"> <li>• present</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Type</li> </ul>	SFB
<ul style="list-style-type: none"> <li>• Number</li> </ul>	Unlimited (limited only by RAM capacity)
<b>Data areas and their retentivity</b>	
Retentive data area (incl. timers, counters, flags), max.	Total working and load memory (with backup battery)
<b>Flag</b>	
<ul style="list-style-type: none"> <li>• Size, max.</li> </ul>	8 kbyte; Size of bit memory address area
<ul style="list-style-type: none"> <li>• Retentivity available</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Retentivity preset</li> </ul>	MB 0 to MB 15
<ul style="list-style-type: none"> <li>• Number of clock memories</li> </ul>	8; in 1 memory byte
<b>Local data</b>	
<ul style="list-style-type: none"> <li>• adjustable, max.</li> </ul>	16 kbyte
<ul style="list-style-type: none"> <li>• preset</li> </ul>	8 kbyte
<b>Address area</b>	
<b>I/O address area</b>	
<ul style="list-style-type: none"> <li>• Inputs</li> </ul>	8 kbyte
<ul style="list-style-type: none"> <li>• Outputs</li> </ul>	8 kbyte
<b>Process image</b>	
<ul style="list-style-type: none"> <li>• Inputs, adjustable</li> </ul>	8 kbyte
<ul style="list-style-type: none"> <li>• Outputs, adjustable</li> </ul>	8 kbyte
<ul style="list-style-type: none"> <li>• Inputs, default</li> </ul>	256 byte
<ul style="list-style-type: none"> <li>• Outputs, default</li> </ul>	256 byte
<ul style="list-style-type: none"> <li>• consistent data, max.</li> </ul>	244 byte
<ul style="list-style-type: none"> <li>• Access to consistent data in process image</li> </ul>	Yes
<b>Subprocess images</b>	
<ul style="list-style-type: none"> <li>• Number of subprocess images, max.</li> </ul>	15
<b>Digital channels</b>	
<ul style="list-style-type: none"> <li>• Inputs</li> </ul>	65 536
<ul style="list-style-type: none"> <li>— of which central</li> </ul>	65 536
<ul style="list-style-type: none"> <li>• Outputs</li> </ul>	65 536
<ul style="list-style-type: none"> <li>— of which central</li> </ul>	65 536
<b>Analog channels</b>	
<ul style="list-style-type: none"> <li>• Inputs</li> </ul>	4 096
<ul style="list-style-type: none"> <li>— of which central</li> </ul>	4 096
<ul style="list-style-type: none"> <li>• Outputs</li> </ul>	4 096
<ul style="list-style-type: none"> <li>— of which central</li> </ul>	4 096
<b>Hardware configuration</b>	
Integrated power supply	No
Number of expansion units, max.	21
connectable OPs	31
Multicomputing	Yes; 4 CPUs max. (with UR1 or UR2)
<b>Interface modules</b>	
<ul style="list-style-type: none"> <li>• Number of connectable IMs (total), max.</li> </ul>	6
<ul style="list-style-type: none"> <li>• Number of connectable IM 460s, max.</li> </ul>	6
<ul style="list-style-type: none"> <li>• Number of connectable IM 463s, max.</li> </ul>	4; IM 463-2
<b>Number of DP masters</b>	
<ul style="list-style-type: none"> <li>• integrated</li> </ul>	2
<ul style="list-style-type: none"> <li>• via CP</li> </ul>	10; CP 443-5 Extended
<ul style="list-style-type: none"> <li>• via IM 467</li> </ul>	4
<ul style="list-style-type: none"> <li>• Mixed mode IM + CP permitted</li> </ul>	No; IM 467 not suitable for use with CP 443-5 Ext. and CP 443-1 EX4x, EX20, GX20 (in PROFINET IO mode)
<ul style="list-style-type: none"> <li>• via interface module</li> </ul>	0
<ul style="list-style-type: none"> <li>• Number of pluggable S5 modules (via adapter capsule in central device), max.</li> </ul>	6
<b>Number of IO Controllers</b>	
<ul style="list-style-type: none"> <li>• integrated</li> </ul>	0
<ul style="list-style-type: none"> <li>• via CP</li> </ul>	4; No mixed operation of CP443-1 EX40 and CP443-1 EX 41/EX20/GX20, max. 4 in central controller
<b>Number of operable FMs and CPs (recommended)</b>	
<ul style="list-style-type: none"> <li>• FM</li> </ul>	Limited by number of slots and number of connections
<ul style="list-style-type: none"> <li>• CP, PtP</li> </ul>	CP 440: Limited by number of slots; CP 441: limited by number of connections

• PROFIBUS and Ethernet CPs	14; Of which 10 CPs max. or IMs as DP master, 4 PROFINET controller maximum
<b>Slots</b>	
• required slots	1
<b>Time of day</b>	
<b>Clock</b>	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
• Resolution	1 ms
• Deviation per day (buffered), max.	1.7 s; Power off
• Deviation per day (unbuffered), max.	8.6 s; For power On
<b>Operating hours counter</b>	
• Number	16
• Number/Number range	0 to 15
• Range of values	SFCs 2, 3 and 4: 0 to 32767 hours SFC 101: 0 to 2 <sup>31</sup> - 1 hours
• Granularity	1 h
• retentive	Yes
<b>Clock synchronization</b>	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• to DP, master	Yes
• to DP, slave	Yes
• in AS, master	Yes
• in AS, slave	Yes
• on Ethernet via NTP	No; Via CP
<b>Time difference in system when synchronizing via</b>	
• MPI, max.	200 ms
<b>Interfaces</b>	
Interfaces/bus type	1 x MPI/PROFIBUS DP, 1 x PROFIBUS DP
Number of RS 485 interfaces	2; Combined MPI / PROFIBUS DP and PROFIBUS DP
Optical interface	No
<b>1. Interface</b>	
Interface type	MPI/PROFIBUS DP
Isolated	Yes
<b>Interface types</b>	
• RS 485	Yes
• Output current of the interface, max.	150 mA
<b>Protocols</b>	
• MPI	Yes
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
<b>MPI</b>	
• Number of connections	32; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1
• Transmission rate, max.	12 Mbit/s
<b>Services</b>	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
<b>PROFIBUS DP master</b>	
• Number of connections, max.	16; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	32
<b>Services</b>	
— PG/OP communication	Yes

— Routing	Yes; S7 routing
— Global data communication	No
— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
— Equidistance	Yes
— Isochronous mode	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
— DPV1	Yes
<b>Address area</b>	
— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte
<b>User data per DP slave</b>	
— User data per DP slave, max.	244 byte
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
<b>PROFIBUS DP slave</b>	
• Number of connections	16
• GSD file	<a href="http://support.automation.siemens.com/WW/view/en/113652">http://support.automation.siemens.com/WW/view/en/113652</a>
• Transmission rate, max.	12 Mbit/s
• automatic baud rate search	No
• Address area, max.	32; Virtual slots
• User data per address area, max.	32 byte
— of which consistent, max.	32 byte
<b>Services</b>	
— PG/OP communication	Yes; with interface active
— Routing	Yes; with interface active
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
— Direct data exchange (slave-to-slave communication)	No
— DPV1	No
<b>Transfer memory</b>	
— Inputs	244 byte
— Outputs	244 byte
<b>2. Interface</b>	
Interface type	PROFIBUS DP
Isolated	Yes
<b>Interface types</b>	
• RS 485	Yes
• Output current of the interface, max.	150 mA
<b>Protocols</b>	
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
<b>PROFIBUS DP master</b>	
• Number of connections, max.	16
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	96
<b>Services</b>	
— PG/OP communication	Yes
— Routing	Yes; S7 routing
— Global data communication	No

— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
— Equidistance	Yes
— Isochronous mode	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
— DPV1	Yes
<b>Address area</b>	
— Inputs, max.	6 kbyte
— Outputs, max.	6 kbyte
<b>User data per DP slave</b>	
— User data per DP slave, max.	244 byte
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
<b>PROFIBUS DP slave</b>	
• Number of connections	16
• GSD file	<a href="http://support.automation.siemens.com/WW/view/en/113652">http://support.automation.siemens.com/WW/view/en/113652</a>
• Transmission rate, max.	12 Mbit/s
• Address area, max.	32
• User data per address area, max.	32 byte
— of which consistent, max.	32 byte
<b>Services</b>	
— Routing	Yes
<b>Transfer memory</b>	
— Inputs	244 byte
— Outputs	244 byte
<b>Protocols</b>	
<b>SIMATIC communication</b>	
• S7 routing	Yes
<b>Open IE communication</b>	
• ISO-on-TCP (RFC1006)	Via CP 443-1 and loadable FB
— Data length, max.	1 452 bytes via CP 443-1 Adv.
<b>Web server</b>	
• supported	No
<b>Isochronous mode</b>	
Equidistance	Yes
Number of DP masters with isochronous mode	2
User data per isochronous slave, max.	244 byte
shortest clock pulse	1 ms; 0.5 ms without use of SFC 126, 127
max. cycle	32 ms
<b>communication functions / header</b>	
<b>PG/OP communication</b>	
• Number of connectable OPs without message processing	31
• Number of connectable OPs with message processing	31; When using Alarm_S/SQ and Alarm_D/DQ
Data record routing	Yes
<b>Global data communication</b>	
• supported	Yes
• Number of GD loops, max.	8
• Number of GD packets, transmitter, max.	8
• Number of GD packets, receiver, max.	16
• Size of GD packets, max.	54 byte
• Size of GD packet (of which consistent), max.	1 variable
<b>S7 basic communication</b>	
• communication function / S7 basic communication	Yes
• User data per job, max.	76 byte

<ul style="list-style-type: none"> <li>• User data per job (of which consistent), max.</li> </ul>	1 variable
<b>S7 communication</b>	
<ul style="list-style-type: none"> <li>• supported</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• as server</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• as client</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• User data per job, max.</li> </ul>	64 kbyte
<ul style="list-style-type: none"> <li>• User data per job (of which consistent), max.</li> </ul>	462 byte; 1 variable
<b>S5 compatible communication</b>	
<ul style="list-style-type: none"> <li>• supported</li> </ul>	Yes; Via FC AG_SEND and AG_RECV, max. via 10 CP 443-1 or 443-5
<ul style="list-style-type: none"> <li>• User data per job, max.</li> </ul>	8 kbyte
<ul style="list-style-type: none"> <li>• User data per job (of which consistent), max.</li> </ul>	240 byte
<ul style="list-style-type: none"> <li>• Number of simultaneous AG-SEND/AG-RECV orders per CPU, max.</li> </ul>	24/24
<b>Standard communication (FMS)</b>	
<ul style="list-style-type: none"> <li>• supported</li> </ul>	Yes; Via CP and loadable FB
<b>Number of connections</b>	
<ul style="list-style-type: none"> <li>• overall</li> </ul>	32
<ul style="list-style-type: none"> <li>• usable for PG communication</li> </ul>	31
<ul style="list-style-type: none"> <li>— reserved for PG communication</li> </ul>	1
<ul style="list-style-type: none"> <li>— adjustable for PG communication, max.</li> </ul>	0
<ul style="list-style-type: none"> <li>• usable for OP communication</li> </ul>	31
<ul style="list-style-type: none"> <li>— reserved for OP communication</li> </ul>	1
<ul style="list-style-type: none"> <li>— adjustable for OP communication, max.</li> </ul>	0
<ul style="list-style-type: none"> <li>• usable for S7 basic communication</li> </ul>	30
<ul style="list-style-type: none"> <li>— reserved for S7 basic communication</li> </ul>	0
<ul style="list-style-type: none"> <li>— adjustable for S7 basic communication, max.</li> </ul>	0
<ul style="list-style-type: none"> <li>• usable for S7 communication</li> </ul>	30
<ul style="list-style-type: none"> <li>— reserved for S7 communication</li> </ul>	0
<ul style="list-style-type: none"> <li>— adjustable for S7 communication, max.</li> </ul>	0
<ul style="list-style-type: none"> <li>• usable for routing</li> </ul>	15
<ul style="list-style-type: none"> <li>— reserved for routing</li> </ul>	0
<ul style="list-style-type: none"> <li>— adjustable for routing, max.</li> </ul>	0
<b>S7 message functions</b>	
Number of login stations for message functions, max.	31; Max. 31 with Alarm_S/SQ and Alarm_D/DQ (OPs); max. 8 with Alarm_8 and Alarm_P (e.g. WinCC)
Symbol-related messages	Yes
SCAN procedure	Yes
Program alarms	Yes
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	400; Simultaneously active alarm_S/SQ blocks or alarm_D/DQ blocks
Alarm 8-blocks	Yes
<ul style="list-style-type: none"> <li>• Number of instances for alarm 8 and S7 communication blocks, max.</li> </ul>	1 200
<ul style="list-style-type: none"> <li>• preset, max.</li> </ul>	300
Process control messages	Yes
Number of archives that can log on simultaneously (SFB 37 AR_SEND)	16
<b>Number of messages</b>	
<ul style="list-style-type: none"> <li>• overall, max.</li> </ul>	512
<ul style="list-style-type: none"> <li>• in 100 ms grid, max.</li> </ul>	128
<ul style="list-style-type: none"> <li>• in 500 ms grid, max.</li> </ul>	256
<ul style="list-style-type: none"> <li>• in 1000 ms grid, max.</li> </ul>	512
<b>Number of additional values</b>	
<ul style="list-style-type: none"> <li>• with 100 ms grid, max.</li> </ul>	1
<ul style="list-style-type: none"> <li>• with 500, 1000 ms grid, max.</li> </ul>	10
<b>Test commissioning functions</b>	
Status block	Yes; Up to 2 simultaneously
Single step	Yes
Number of breakpoints	4
<b>Status/control</b>	
<ul style="list-style-type: none"> <li>• Status/control variable</li> </ul>	Yes; Up to 16 variable tables
<ul style="list-style-type: none"> <li>• Variables</li> </ul>	Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters

• Number of variables, max.	70; Status/control
<b>Forcing</b>	
• Forcing	Yes
• Forcing, variables	Inputs, outputs, bit memories, peripheral inputs, peripheral outputs
• Number of variables, max.	256
<b>Diagnostic buffer</b>	
• present	Yes
• Number of entries, max.	400
— adjustable	Yes
— preset	120
<b>Service data</b>	
• can be read out	Yes
<b>Standards, approvals, certificates</b>	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
<b>Use in hazardous areas</b>	
• ATEX	ATEX II 3G Ex nA IIC T4 Gc
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• min.	0 °C
• max.	60 °C
<b>configuration / header</b>	
<b>Configuration software</b>	
• STEP 7	Yes
<b>configuration / programming / header</b>	
• Command set	see instruction list
• Nesting levels	7
• Access to consistent data in process image	Yes
• System functions (SFC)	see instruction list
• System function blocks (SFB)	see instruction list
<b>Programming language</b>	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
— HiGraph®	Yes
<b>configuration / programming / number of simultaneously active SFC / header</b>	
— DPSYC_FR	2; SFC 11; per interface
— D_ACT_DP	8; SFC 12; per interface
— RD_REC	8; SFC 59; per interface
— WR_REC	8; SFC 58; per interface
— WR_PARM	8; SFC 55; per interface
— PARM_MOD	1; SFC 57; per interface
— WR_DPARM	2; SFC 56; per interface
— DPNRM_DG	8; SFC 13; per interface
— RDSYSST	8
— DP_TOPOL	1; SFC 103; per interface
<b>configuration / programming / number of simultaneously active SFB / header</b>	
— RDREC	8; SFB 52; per interface, but not more than 32 across all external interfaces
— WRREC	8; SFB 53; per interface, but not more than 32 across all external interfaces
<b>Know-how protection</b>	
• User program protection/password protection	Yes



Dimensions	
Width	25 mm
Height	290 mm
Depth	219 mm
Weights	
Weight, approx.	700 g

**last modified:** 9/11/2023 