



SIMATIC ET 200SP, Analog input module, AI 4xRTD/TC High Feature, suitable for BU type A0, A1, Color code CC00, channel diagnostics, 16 bit, +/-0.1%, 2-/3-/4-wire

General information	
Product type designation	AI 4xRTD/TC 2-/3-/4-wire HF
Firmware version	V2.1
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
usable BaseUnits	BU type A0, A1
Color code for module-specific color identification plate	CC00
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	No
<ul style="list-style-type: none"> <li>Adjustment of measuring range</li> </ul>	Yes
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V12 SP1 / V13
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>	V5.5 SP3 / V5.5 SP4
<ul style="list-style-type: none"> <li>PCS 7 configurable/integrated from version</li> </ul>	V8.1 SP1
<ul style="list-style-type: none"> <li>PROFIBUS from GSD version/GSD revision</li> </ul>	GSD Revision 5
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	GSDML V2.3
CIR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	30 mA
Current consumption, max.	32 mA
Power loss	
Power loss, typ.	0.75 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Address space per module, max.</li> </ul>	8 byte; + 1 byte for QI information
Hardware configuration	
Automatic encoding	
<ul style="list-style-type: none"> <li>Type of mechanical coding element</li> </ul>	Type A
Analog inputs	
Number of analog inputs	4
permissible input voltage for voltage input (destruction limit), max.	30 V
Constant measurement current for resistance-type transmitter,	2 mA

typ.	
Cycle time (all channels), min.	Sum of the basic conversion times and additional processing times (depending on the parameterization of the active channels); for line compensation in case of a three-wire connection, an additional cycle is necessary
Technical unit for temperature measurement adjustable	Yes; °C/°F/K
<b>Input ranges (rated values), voltages</b>	
<ul style="list-style-type: none"> <li>● -1 V to +1 V <ul style="list-style-type: none"> <li>— Input resistance (-1 V to +1 V)</li> </ul> </li> <li>● -250 mV to +250 mV <ul style="list-style-type: none"> <li>— Input resistance (-250 mV to +250 mV)</li> </ul> </li> <li>● -50 mV to +50 mV <ul style="list-style-type: none"> <li>— Input resistance (-50 mV to +50 mV)</li> </ul> </li> <li>● -80 mV to +80 mV <ul style="list-style-type: none"> <li>— Input resistance (-80 mV to +80 mV)</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> </ul>
<b>Input ranges (rated values), thermocouples</b>	
<ul style="list-style-type: none"> <li>● Type B <ul style="list-style-type: none"> <li>— Input resistance (Type B)</li> </ul> </li> <li>● Type C <ul style="list-style-type: none"> <li>— Input resistance (Type C)</li> </ul> </li> <li>● Type E <ul style="list-style-type: none"> <li>— Input resistance (Type E)</li> </ul> </li> <li>● Type J <ul style="list-style-type: none"> <li>— Input resistance (type J)</li> </ul> </li> <li>● Type K <ul style="list-style-type: none"> <li>— Input resistance (Type K)</li> </ul> </li> <li>● Type L <ul style="list-style-type: none"> <li>— Input resistance (Type L)</li> </ul> </li> <li>● Type N <ul style="list-style-type: none"> <li>— Input resistance (Type N)</li> </ul> </li> <li>● Type R <ul style="list-style-type: none"> <li>— Input resistance (Type R)</li> </ul> </li> <li>● Type S <ul style="list-style-type: none"> <li>— Input resistance (Type S)</li> </ul> </li> <li>● Type T <ul style="list-style-type: none"> <li>— Input resistance (Type T)</li> </ul> </li> <li>● Type U <ul style="list-style-type: none"> <li>— Input resistance (Type U)</li> </ul> </li> <li>● Type TXK/TXK(L) to GOST <ul style="list-style-type: none"> <li>— Input resistance (Type TXK/TXK(L) to GOST)</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> </ul>
<b>Input ranges (rated values), resistance thermometer</b>	
<ul style="list-style-type: none"> <li>● Cu 10 <ul style="list-style-type: none"> <li>— Input resistance (Cu 10)</li> </ul> </li> <li>● Ni 100 <ul style="list-style-type: none"> <li>— Input resistance (Ni 100)</li> </ul> </li> <li>● Ni 1000 <ul style="list-style-type: none"> <li>— Input resistance (Ni 1000)</li> </ul> </li> <li>● LG-Ni 1000 <ul style="list-style-type: none"> <li>— Input resistance (LG-Ni 1000)</li> </ul> </li> <li>● Ni 120 <ul style="list-style-type: none"> <li>— Input resistance (Ni 120)</li> </ul> </li> <li>● Ni 200 <ul style="list-style-type: none"> <li>— Input resistance (Ni 200)</li> </ul> </li> <li>● Ni 500 <ul style="list-style-type: none"> <li>— Input resistance (Ni 500)</li> </ul> </li> <li>● Pt 100 <ul style="list-style-type: none"> <li>— Input resistance (Pt 100)</li> </ul> </li> <li>● Pt 1000 <ul style="list-style-type: none"> <li>— Input resistance (Pt 1000)</li> </ul> </li> <li>● Pt 200 <ul style="list-style-type: none"> <li>— Input resistance (Pt 200)</li> </ul> </li> <li>● Pt 500 <ul style="list-style-type: none"> <li>— Input resistance (Pt 500)</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> </ul>

— Input resistance (Pt 500)	1 MΩ
<b>Input ranges (rated values), resistors</b>	
● 0 to 150 ohms	Yes; 15 bit
— Input resistance (0 to 150 ohms)	1 MΩ
● 0 to 300 ohms	Yes; 15 bit
— Input resistance (0 to 300 ohms)	1 MΩ
● 0 to 600 ohms	Yes; 15 bit
— Input resistance (0 to 600 ohms)	1 MΩ
● 0 to 3000 ohms	Yes; 15 bit
— Input resistance (0 to 3000 ohms)	1 MΩ
● 0 to 6000 ohms	Yes; 15 bit
— Input resistance (0 to 6000 ohms)	1 MΩ
● PTC	Yes; 15 bit
— Input resistance (PTC)	1 MΩ
<b>Thermocouple (TC)</b>	
<b>Temperature compensation</b>	
— parameterizable	Yes
— Reference channel of the module	Yes
— internal comparison point	Yes; with BaseUnit type A1
— Number of reference channel groups	4; Group 0 to 3
<b>Cable length</b>	
● shielded, max.	200 m; 50 m with thermocouples
<b>Analog value generation for the inputs</b>	
Measurement principle	integrating (Sigma-Delta)
<b>Integration and conversion time/resolution per channel</b>	
● Resolution with overrange (bit including sign), max.	16 bit
● Integration time, parameterizable	Yes
● Basic conversion time, including integration time (ms)	
— additional processing time for wire-break check	2 ms; In the ranges resistance thermometers, resistors and thermocouples
— additional power line wire-break check	2 ms; for 3/4 wire transducer (resistance thermometer and resistor)
● Interference voltage suppression for interference frequency $f_1$ in Hz	16.6 / 50 / 60 Hz
● Conversion time (per channel)	180 / 60 / 50 / (67.5 / 22.5 / 18.75) ms
<b>Smoothing of measured values</b>	
● Number of smoothing levels	4; None; 4/8/16 times
● parameterizable	Yes
<b>Encoder</b>	
<b>Connection of signal encoders</b>	
● for voltage measurement	Yes
● for resistance measurement with two-wire connection	Yes
● for resistance measurement with three-wire connection	Yes
● for resistance measurement with four-wire connection	Yes
<b>Errors/accuracies</b>	
Linearity error (relative to input range), (+/-)	0.01 %; ±0.1 % for resistance thermometers and resistance
Temperature error (relative to input range), (+/-)	0.0009 %/K; ±0.005 % / K at thermocouple
Crosstalk between the inputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.05 %
<b>Operational error limit in overall temperature range</b>	
● Voltage, relative to input range, (+/-)	0.1 %
● Resistance, relative to input range, (+/-)	0.1 %
<b>Basic error limit (operational limit at 25 °C)</b>	
● Voltage, relative to input range, (+/-)	0.05 %
● Resistance, relative to input range, (+/-)	0.05 %
<b>Interference voltage suppression for <math>f = n \times (f_1 \pm 1 \%)</math>, <math>f_1 =</math> interference frequency</b>	
● Series mode interference (peak value of interference < rated value of input range), min.	70 dB; With conversion time 67.5 / 22.5 / 18.75 ms: 40 dB
● common mode voltage / with interference voltage suppression / maximum	10 V
● Common mode interference, min.	90 dB
<b>Interrupts/diagnostics/status information</b>	
<b>Alarms</b>	

• Limit value alarm	Yes; two upper and two lower limit values in each case
<b>Diagnoses</b>	
• Monitoring the supply voltage	Yes
• Wire-break	Yes; channel by channel
• Group error	Yes
• Overflow/underflow	Yes; channel by channel
<b>Diagnostics indication LED</b>	
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• Channel status display	Yes; green LED
• for channel diagnostics	Yes; red LED
• for module diagnostics	Yes; green/red DIAG LED
<b>Isolation</b>	
Isolation tested with	707 V DC (type test)
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• horizontal installation, min.	-30 °C; < 0 °C as of FS08
• horizontal installation, max.	60 °C
• vertical installation, min.	-30 °C; < 0 °C as of FS08
• vertical installation, max.	50 °C
<b>Dimensions</b>	
Width	15 mm
Height	73 mm
Depth	58 mm

**last modified:**

4/25/2024 