

Draw-out circuit breaker with slide-in module frame 4-pole, Size 2, IEC In=2000 A to 690 V, 50/60 Hz AC Icu=66 kA at 500 V Rear horizontal connection

| Model                                                                                                                         |            |
|-------------------------------------------------------------------------------------------------------------------------------|------------|
| design of the actuating element                                                                                               | Pushbutton |
| General technical data                                                                                                        |            |
| size of the circuit-breaker                                                                                                   | 2          |
| utilization category                                                                                                          | B          |
| Voltage                                                                                                                       |            |
| Rated insulation voltage Ui                                                                                                   | 1 000 V    |
| operating voltage                                                                                                             |            |
| <ul style="list-style-type: none"> <li>for main current circuit / at AC / at 50 Hz / according to UL 489 / maximum</li> </ul> | 600 V      |
| <ul style="list-style-type: none"> <li>for main current circuit / at AC / at 60 Hz / according to UL 489 / maximum</li> </ul> | 600 V      |
| Protection class                                                                                                              |            |
| protection class IP                                                                                                           | IP20       |
| Mechanical Design                                                                                                             |            |
| Net Weight                                                                                                                    | 109 kg     |
| Environmental conditions                                                                                                      |            |
| ambient temperature / during storage                                                                                          |            |
| <ul style="list-style-type: none"> <li>minimum</li> </ul>                                                                     | -40 °C     |
| Further information                                                                                                           |            |

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL1220-2..76-....>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WL1220-2..76-....>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3WL1220-2..76-....](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1220-2..76-....)

### CAX-Online-Generator

<https://www.siemens.com/cax>

### Tender specifications

<https://www.siemens.com/specifications>

### Kennlinien

<https://curves.simarisiemens.com/curves/3WL1220-2..76-....>



last modified:

9/2/2025

