



CONTACTOR, AC-3 15 KW/400 V, AC 230 V, 50 HZ, 3-POLE, SIZE S2, SCREW CONNECTION

Figure similar

product brand name		SIRIUS
Product designation		power contactor

General technical data:

Insulation voltage		
• Rated value	V	690
Degree of pollution		3
Surge voltage resistance Rated value	kV	6
Mechanical service life (switching cycles)		
• of the contactor typical		10 000 000
• of the contactor with added electronics-compatible auxiliary switch block typical		5 000 000
• of the contactor with added auxiliary switch block typical		10 000 000
Thermal short-time current restricted to 10 s	A	320
Protection class IP		
• on the front		IP00
• of the terminal		IP00
Equipment marking		
• acc. to DIN EN 61346-2		Q
• acc. to DIN EN 81346-2		Q

Main circuit:

Number of poles for main current circuit		3
Number of NC contacts for main contacts		0
Number of NO contacts for main contacts		3
Operating current		

• at AC-1 — at 400 V at ambient temperature 40 °C Rated value — up to 690 V at ambient temperature 40 °C Rated value — up to 690 V at ambient temperature 60 °C Rated value • at AC-3 — at 400 V Rated value — at 690 V Rated value • at AC-4 at 400 V Rated value	A	50
	A	50
	A	45
	A	32
	A	20
	A	29
Operating current with 1 current path		
• at DC-1 — at 24 V Rated value — at 110 V Rated value • at DC-3 at DC-5 — at 24 V Rated value — at 110 V Rated value	A	45
	A	4.5
	A	35
	A	2.5
Operating current with 2 current paths in series		
• at DC-1 — at 24 V Rated value — at 110 V Rated value • at DC-3 at DC-5 — at 110 V Rated value — at 24 V Rated value	A	45
	A	25
	A	25
	A	45
Operating current with 3 current paths in series		
• at DC-1 — at 24 V Rated value — at 110 V Rated value • at DC-3 at DC-5 — at 110 V Rated value — at 24 V Rated value	A	45
	A	45
	A	45
	A	45
Operating power		
• at AC-1 — at 230 V at 60 °C Rated value — at 690 V at 60 °C Rated value	kW	18
	kW	54
Operating power for ≥ 200000 operating cycles at AC-4		
• at 400 V Rated value • at 690 V Rated value	kW	8.2
	kW	10
Active power loss at AC-3 at 400 V for rated value of the operating current per conductor		
	W	1.8

Operating frequency • at AC-1 maximum • at AC-2 maximum • at AC-3 maximum • at AC-4 maximum	1/h	1 200
	1/h	750
	1/h	1 000
	1/h	250
No-load switching frequency • with AC	1/h	5 000

Control circuit/ Control:

Type of voltage of the control supply voltage		AC
Control supply voltage with AC • at 50 Hz Rated value • Rated value	V Hz	230 50
Operating range factor control supply voltage rated value of the magnet coil with AC • at 50 Hz		0.8 ... 1.1

Auxiliary circuit:

Number of NC contacts • for auxiliary contacts — instantaneous contact		0
Number of NO contacts • for auxiliary contacts — instantaneous contact		0
Operating current at AC-15 • at 230 V Rated value • at 400 V Rated value	A A	6 3
Contact reliability of the auxiliary contacts		1 faulty switching per 100 million (17 V, 1 mA)

UL/CSA ratings:

Contact rating of the auxiliary contacts acc. to UL		A600 / Q600
--	--	-------------

Short-circuit:

Design of the fuse link • for short-circuit protection of the main circuit — with type of assignment 1 required — with type of assignment 2 required • for short-circuit protection of the auxiliary switch required		fuse gL/gG: 125 A fuse gL/gG: 63 A fuse gL/gG: 10 A
---	--	---

Installation/ mounting/ dimensions:

Mounting type • Side-by-side mounting		screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022 Yes
Height	mm	112
Width	mm	55

Depth	mm	115
Required spacing		
• for grounded parts		
— at the side	mm	6

Connections/ Terminals:

Type of electrical connection		
• for main current circuit		screw-type terminals
• for auxiliary and control current circuit		screw-type terminals
Type of connectable conductor cross-section		
• for main contacts		
— solid		2x (0.75 ... 16 mm ²)
— stranded		2x (0.75 ... 25 mm ²)
— single or multi-stranded		2x (0,75 ... 16 mm ²)
— finely stranded with core end processing		2x (0.75 ... 16 mm ²)
— finely stranded without core end processing		2x (0.75 ... 16 mm ²)
• for AWG conductors for main contacts		2x (18 ... 2)
• for auxiliary contacts		
— solid		2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²), max. 2x (0.75 ... 4 mm ²)
— finely stranded with core end processing		2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²)
• for AWG conductors for auxiliary contacts		2x (20 ... 16), 2x (18 ... 14), 1x 12

Mechanical data:

Size of contactor		S2
--------------------------	--	----

Ambient conditions:

Installation altitude at height above sea level maximum	m	2 000
Ambient temperature		
• during operation	°C	-25 ... +60
• during storage	°C	-55 ... +80

Certificates/ approvals:

General Product Approval	Functional Safety/Safety of Machinery	Declaration of Conformity	Test Certificates
--------------------------	---------------------------------------	---------------------------	-------------------



CSA



UL



[Type Examination](#)



EG-Konf.

[Type Test Certificates/Test Report](#)

Test Certificates	Shipping Approval
-------------------	-------------------

[Special Test Certificate](#)



ABS



DNV



GL



LRS



RINA

Shipping Approval	other
-------------------	-------



RMRS

[Confirmation](#)

[Environmental Confirmations](#)

[other](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT10341AP00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT10341AP00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT10341AP00&lang=en



last modified:

14.04.2015